D. Wedding Shopping

Patricia Smith and José Antonio Sánchez request the pleasure of the company of *Mr and Mrs James and Sarah Student* at their wedding, at St Mary's Church, Espinardo on Saturday, May 17th, 2008 at 9 o'clock and afterwards at Cantina Hall, CSU. RSVP Universitary Campus, Espinardo, WT8 4EG

Background

One of our best friends is getting married and we all are nervous because he is the first of us who is doing something similar. In fact, we have never assisted to a wedding, so we have no clothes or accessories, and to solve the problem we are going to a famous department store of our city to buy all we need: a shirt, a belt, some shoes, a tie, etcetera.

The Problem

We are offered different models for each class of garment (for example, three shirts, two belts, four shoes, ..). We have to buy one model of each class of garment, and just one.

As our budget is limited, we cannot spend more money than it, but we want to spend the maximum possible. It's possible that we cannot buy one model of each class of garment due to the short amount of money we have.

The Input

The first line of the input contains an integer, N, indicating the number of test cases. For each test case, some lines appear, the first one contains two integers, M and C, separated by blanks (1<=M<=200, and 1<=C<=20), where M is the available amount of money and C is the number of garments you have to buy. Following this line, there are C lines, each one with some integers separated by blanks; in each of these lines the first integer, K (1<=K<=20), indicates the number of different models for each garment and it is followed by K integers indicating the price of each model of that garment.

The Output

For each test case, the output should consist of one integer indicating the maximum amount of money necessary to buy one element of each garment without exceeding the initial amount of money. If there is no solution, you must print "no solution".

Sample Input

Sample Output

75 19 no solution